

CEWELD AA 2594M

TYPE Metal cored wire designed for welding 25Cr type duplex stainless

TOEPASSINGEN Duplex stainless steels in chemical industry such as offshore, tubing, vessel, boilers etc

EIGENSCHAPPEN AA 2594M is a metal cored wire designed for welding 25Cr type duplex stainless steels especially for Super Duplex grade. Excellent productivity, improved weldability, better wetting properties compared to solid wires. Excellent weld metal quality and X-ray soundness

CLASSIFICATIE

AWS	A 5.22: ~E2594T1-1
EN ISO	17633-A: T 25 9 4 Cu N L M M12 1
W.Nr.	1.4410
F-nr	6
FM	5

GESCHIKT VOOR 1.4507, 1.4410, 1.4468, 1.4515, 1.4517, 1.4501, 1.4467, 1.4569, 1.4508
 X2 CrNiMoCuN 25-6-3, X2 CrNiMoN 25-7-4, GX2 CrNiMoN 25-6-3, GX2 CrNiMoCuN 26-6-3, GX2 CrNiMoCuN 25-6-3-3, X2 CrNiMoCuWN 25-7-4, X2CrMnNiMoN26-5-4, X 2 CrNiMoN 26 7 4, GX2CrNiMoCuWN25-8-4
 UNS S32520, S32550, S32750, S39274, S39277, S39553, S32760, J93380
 Ferralium 255, SAF 2507, ZERON 100, UR 76 N, SM22Cr, SAF 2507, Alloy 2507, Alloy 2594, Super Duplex

GOEDKEURINGEN CE

LASPOSITIES



TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)


C	Si	Mn	P	Cr	Ni	Mo	N	Cu	S
0.025	0.6	1.4	0.025	25.5	9	3.5	0.25	0.6	0.015

MECHANISCHE WAARDEN

Heat Treatment	R _{P0,2} (MPa)	R _m (MPa)	A ₅ (%)	Impact Energy (J) ISO-V	Hardness
				-46°C	
As Welded	580	680	20	40	HRC

HERDROGEN Not required

GAS ACC. EN ISO 14175 M21



CEWELD AA 2594M

AA 2594M 1,2MM

Packaging	KG/unit	EanCode
BS-300	15	8720663414786